US006400917B2

(12) **United States Patent**
Nakazato et al.

(10) **Patent No.: US 6,400,917 B2**
(45) **Date of Patent: Jun. 4, 2002**

(54) **IMAGE FORMING APPARATUS FOR REDUCING BANDING CAUSED BY VIBRATION OF STACKED IMAGE FORMING CARTRIDGES**

(75) Inventors: **Yasushi Nakazato**; **Kazuyuki Shimada**; **Tomohiro Nakajima**, all of Tokyo (JP)

(73) Assignee: **Ricoh Company, Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/805,246**

(22) Filed: **Mar. 14, 2001**

Related U.S. Application Data

(62) Division of application No. 09/305,275, filed on May 5, 1999, now Pat. No. 6,236,820.

(30) **Foreign Application Priority Data**

May 7, 1998 (JP) 10-124640
May 12, 1998 (JP) 10-128728
Apr. 7, 1999 (JP) 11-099724

(51) **Int. Cl.**[7] **G03G 21/16**
(52) **U.S. Cl.** **399/111**; 347/232; 347/257; 399/110; 399/112

(58) **Field of Search** 399/110, 111, 399/112, 118, 107, 126, 178, 179, 177; 347/138, 152, 245, 263, 232, 257

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,208,640 A * 5/1993 Horie et al.
5,752,137 A * 5/1998 Haneda
5,787,324 A * 7/1998 Iwasaki 399/112
5,848,329 A * 12/1998 Aoyama et al. ..... 399/111 X
5,907,749 A * 5/1999 Nomura et al.
5,953,559 A * 9/1999 Obu 399/110
6,191,801 B1 * 2/2001 Hiraoka et al. 347/232
6,249,305 B1 * 6/2001 Miyamoto et al. 347/232

* cited by examiner

Primary Examiner—Susan S. Y. Lee
(74) *Attorney, Agent, or Firm*—Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

(57) **ABSTRACT**

An image forming apparatus including a plurality of image forming cartridges removably mounted to an apparatus body one above the other is disclosed. Structural members each partition off a space between nearby image forming cartridges mounted to the apparatus body. The apparatus is capable of obviating banding ascribable to the vibration of the cartridges.

18 Claims, 36 Drawing Sheets




22b
15K'
15K
15C'
15C
15M'
15M
15Y'
15Y
25
8K
8C
8M
8Y
16K
17K
16C
17C
16M
17M
16Y
17Y
22a
4
5
6
7
MOUNTING & DISMOUNTING

Fig. 1B

12K
8K
17K
12C
8C
17C
12M
8M
17M
12Y
8Y
17Y
1
9K
10K
11K
13K
14K
9C
10C
11C
13C
14C
9M
10M
11M
13M
14M
9Y
10Y
11Y
13Y
14Y
25
16K
16C
16M
16Y
4
5
6
7

Fig. 1A


22b
15K'
15K
15C'
15C
15M'
15M
15Y'
15Y
27K
27C
27M
27Y
25
8K
8C
8M
8Y
16K
17K
16C
17C
16M
17M
16Y
17Y
22a
4
5
6
7
MOUNTING & DISMOUNTING

Fig. 2B


12K
8K
17K
12C
8C
17C
12M
8M
17M
12Y
8Y
17Y
1
9K
10K
11K
13K
14K
26K
27K
9C
10C
11C
13C
14C
26C
27C
9M
10M
11M
13M
14M
26M
27M
9Y
10Y
11Y
13Y
14Y
26Y
27Y
25
16K
4
16C
5
16M
6
16Y
7

Fig. 2A


Fig. 3A
Fig. 3B
MOUNTING & DISMOUNTING


Fig. 4A
Fig. 4B
MOUNTING & DISMOUNTING

Fig. 5B


22b
15K'
15K
15C'
15C
15M'
15M
15Y'
15Y
25
8K'
8C'
8M'
8Y'
16K
17K
16C
17C
16M
17M
16Y
17Y
22a
4
5
6
7
MOUNTING & DISMOUNTING

Fig. 5A


12K
8K
10K
11K
17K
12C
8C
10C
11C
17C
12M
8M
10M
11M
17M
12Y
8Y
10Y
11Y
17Y
9K
13K
14K
9C
13C
14C
9M
13M
14M
9Y
13Y
14Y
25
4
5
6
7
30
16K
16C
16M
16Y
Lb
22e
22f

Fig. 6


25(202)
28U(280U)
28b
28a
28D(280D)
28b
28a
MOUNTING & DISMOUNTING

Fig. 7


29

Fig. 8



Fig. 9


111K
112K
Lb
106K
104K
108K
110K
8K
4
202
106C
111C
112C
Lb
8C
104C
108C
110C
5
1
202
111M
112M
Lb
8M
106M
104M
108M
110M
6
202
111Y
112Y
Lb
106Y
8Y
104Y
108Y
110Y
7

Fig. 10


328a
328C
22b
202
5
Lb
22c
104C
Lb
22f
22d
330
22a

Fig. 11


P1
22e
22b
22d
330K
104K
328K
202
330C
104C
328C
22a
202
330M
104M
328M
202
330Y
104Y
328Y
22f
P2

Fig. 12


104K
280U
5
6
202
280D
Lb
8C
104C
7
202
Lb
280U
8M
280D
104M
8
202
104Y
280U
280D

Fig. 13


280U
28b
28a
202
330C
28a
28b
104C
280D
328C
22b
22a
202
330M
280U
280D
104M
328M
280U
280D
202

Fig. 14


5
104K
29U
6
202
29D
Lb
104C
8C
7
202
29U
29D
Lb
104M
8M
8
202
29D
104Y
29U

Fig. 15


29U
330C
29D
202
104C
328C
22b
22a
29U
330M
202
29D
104M
29U
328M
202
29D

Fig. 16


22d
202
202b
300
202a
210'
5
30d
311
312
Lb
8C
104C
306
308
310
210'
202a
202b
6
202
Lb
104M
30d
8M
202a
202
202b
210'

Fig. 17


202c
202c
202c
202
202b
330
104C
328C
22a
22b
202
330
104M
328M
202c
202

Fig. 18


202
25
5
22d
104C
202
30d
25
6
104M
202
30d
25
7
104Y
30

Fig. 19


22e
202
30
30d
25
22c
104K
4
22d
202
Lb
25
104C
5
202
30d
25
104M
6
202
30d
25
104Y
7
202
30d
25
22f

Fig. 20


22
22e
14K
13K
12K
4
104K
Lb
9K
8K
22c
10K
22d
35
11K
Lb
104C
5
35
Lb
6
104M
35
Lb
7
104Y
35
22f

Fig. 21


Lb
4
104K
35
35a
5
104C
Lb
35a
35
6
104M
Lb
35a
35
Lb
7
104Y
35a
35
30(300)

Fig. 22


104K'
Lb
111K
106K
108K
110K

Fig. 23



Fig. 24



Fig. 25A



Fig. 25B



Fig. 26



Fig. 27


22
22e
22d
22c
104K'
47
Lb
4
104C'
47
Lb
5
104M'
47
Lb
6
104Y'
47
Lb
7
300(30)
22f

Fig. 28


22
22e
22b
50
25
25
25
22d
51
51
22c
22a
22f

Fig. 29


22e
22b
25
25
25
54
51
22d
55
51
22c
56
51
51
57
22a
22f

Fig. 30


22
22e
4
5
6
1
7
58
22c
22a
22f

Fig. 31


22
59
22e
22d
4
100
5
59
6
22c
100
7
60
22f

Fig. 32


22
22b
102
5
Lb
22d
22c
8C
100
Lb
22a

Fig. 33



Fig. 34A



Fig. 34B



Fig. 35


22
22b
92a
92
94
5
Lb
22d
100
8C
22c
94
Lb
22a
92a

Fig. 36


22
92a
22e
94
92
4
8K
22d
100K
22c
100
5
8C
100C
6
8M
100M
7
8Y
100Y
94
92a
22f

Fig. 37



Fig. 38



Fig. 39



Fig. 40


22
22b
25
92
92a
5
94
Lb
22d
22c
100
8C
94
Lb
22a
92a

Fig. 41


22
92a
92
22e
94
25
8K
100K
4
22d
100
25
22c
100C
5
8C
25
100M
6
8M
25
100Y
7
8Y
94
92a
22f

Fig. 42



Fig. 43A



Fig. 43B



Fig. 43C



Fig. 43D



Fig. 44


PAPER OUTLET
PAPER INLET
104K
104C
104M
104Y
111K
112K
106K
108K
110K
111C
112C
106C
108C
110C
111M
112M
106M
108M
110M
111Y
112Y
106Y
108Y
110Y
Lb
16K
16C
16M
16Y
9K 12K
10K
8K
14K
13K
11K
4
17K
9C 12C
10C
8C
14C
13C
11C
5
17C
9M 12M
10M
8M
14M
13M
11M
6
17M
9Y 12Y
10Y
8Y
14Y
13Y
11Y
7
17Y
2
1
3
18

Fig. 45



Fig. 46


22
22d
22e
16K
17K
16C
17C
16M
17M
16Y
17Y
22a
4
15K
8K
15K'
5
8C
15C'
6
15C
22b
8M
15M'
7
15M
8Y
15Y'
15Y
22f

Fig. 47


16C
5
MOUNTING &
DISMOUNTING
17C
8C
15C

Fig. 48


16C
5
MOUNTING
&
DISMOUNTING
15C
17C
8C

Fig. 49


16C'
22a
16C
5
MOUNTING
&
DISMOUNTING
15C'
C
17C
15C
17C'

Fig. 50



Fig. 51



Fig. 52A



Fig. 52B



Fig. 52C



Fig. 52D



Fig. 53A



Fig. 53B



Fig. 54


W
328a
22b
328C
5
22d
8C
22c
Lb
104C
Lb
22f
330C
22a
W

Fig. 55


22e
104K
326
328K
330K
104C
22b
330C
328C
22a
104M
330M
328M
104Y
330Y
328Y
22f

Fig. 56A



Fig. 56B



IMAGE FORMING APPARATUS FOR REDUCING BANDING CAUSED BY VIBRATION OF STACKED IMAGE FORMING CARTRIDGES

This application is a Division of application Ser. No. 09/305,275 filed on May 5, 1999 now U.S. Pat. No. 6,236,820.

BACKGROUND OF THE INVENTION

The present invention relates to an image forming apparatus including a plurality of image forming cartridges arranged one above the other and a plurality of optical writing means arranged one above the other or a single optical writing means.

There has been known an image forming apparatus of the type including an apparatus body and a plurality of image forming cartridges removably mounted to the apparatus body one above the other, or stacked, in the direction of gravity. This type of image forming apparatus forms an image with image forming means when the image forming cartridges are mounted to the apparatus body. Photoconductive elements each are supported by either one of the respective image forming cartridge or the apparatus body beforehand. In the case where the photoconductive elements are supported by the apparatus body, the image forming means arranged on the cartridges contact the photoconductive elements when the cartridges are mounted to the apparatus body.

The prerequisite with the image forming apparatus of the type described is that the image forming cartridges removable from the apparatus body be stably positioned on the apparatus body. Should the cartridges be unstable in position, so-called banding would occur in an image due to the vibration of a driveline. Further, optical writing means are stacked one above the other and respectively associated with the cartridges. The optical writing means are also susceptible to the vibration of the driveline, aggravating the banding.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide an image forming apparatus capable of obviating banding ascribable to the vibration of image forming cartridges and that of optical writing means.

In accordance with the present invention, an image forming apparatus for forming an image on a photoconductive element with image forming means includes an apparatus body, a plurality of image forming cartridges removably mounted to the apparatus body in the form of a stack, and a structural member for partitioning off the space between nearby image forming cartridges mounted to the apparatus body. A of photoconductive elements each are supported by the respective image forming cartridge beforehand, or the photoconductive elements are supported by the apparatus body beforehand such that when the image forming cartridges are mounted to the apparatus body, the image forming means supported by the image forming cartridges beforehand each partly contact the associated photoconductive element.

Also, in accordance with the present invention, an image forming apparatus includes an apparatus body, and a plurality of optical writing means stacked one above the other and each being mounted on a respective base member supported by the apparatus body. Adjusting means is included in at least one of the optical writing means for correcting the shift of a scanning line relative to the scanning lines of the other optical writing means. A structural member partitions off the space between the optical writing means including the adjusting means and the optical writing means adjoining it. The structural member is affixed to the apparatus body at a part thereof.

Further, in accordance with the present invention, an image forming apparatus includes an apparatus body, and a plurality of photoconductive elements mounted on the apparatus body one above the other. A plurality of optical writing means each form a latent image on a respective photoconductive element. The optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward the photoconductive elements. The writing unit is spaced from the photoconductive elements by a preselected distance.

Moreover, in accordance with the present invention, an image forming apparatus for forming an image on a photoconductive element with image forming means includes an apparatus body, a plurality of image forming cartridges removably mounted to the apparatus body in the form of a stack, and a plurality of optical writing means each for forming a latent image on a photoconductive element associated herewith. A plurality of photoconductive elements each are supported by a respective one of the plurality of image forming cartridges beforehand, or the photoconductive elements are supported by the apparatus body beforehand such that when the image forming cartridges are mounted to the apparatus body, the image forming means supported by the image forming cartridges beforehand each partly contact associated one of the photoconductive elements. The optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward the photoconductive elements in a stacking direction of the image forming cartridges. The writing unit is spaced from the photoconductive elements by a preselected distance.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

FIG. **1A** is a fragmentary front view showing an image forming apparatus representative of a first example of a first embodiment;

FIG. **1B** is a fragmentary side elevation of the first example;

FIG. **2A** is a fragmentary front view showing an image forming apparatus representative of a second example of the first embodiment;

FIG. **2B** is a fragmentary side elevation of the second example;

FIG. **3A** is a fragmentary front view showing an image forming apparatus representative of a third example of the first embodiment;

FIG. **3B** is a fragmentary side elevation of the third example;

FIG. **4A** is a fragmentary front view showing an image forming apparatus representative of a fourth example of the first embodiment;

FIG. **4B** is a fragmentary side elevation of the fourth example;

FIG. **5A** is a fragmentary front view showing an image forming apparatus representative of a fifth example of the first embodiment;

FIG. **5**B is a fragmentary side elevation view of the fifth example;

FIG. **6** is a perspective view of a horizontal stay;

FIG. **7** is a perspective view of a vibration-proof rubber block;

FIG. **8** is a perspective view of a vertical stay;

FIG. **9** is a fragmentary front view showing a first example of a second embodiment of the present invention;

FIG. **10** is a plan view of the first example shown in FIG. **9**;

FIG. **11** is a side elevation of the first example shown in FIG. **9**;

FIG. **12** is a fragmentary plan view showing a second example of the second embodiment;

FIG. **13** is a side elevation of the second example shown in FIG. **12**;

FIG. **14** is a fragmentary view showing a third example of the second embodiment;

FIG. **15** is a side elevation of the third example shown in FIG. **14**;

FIG. **16** is a fragmentary view showing a first example of a third embodiment of the present invention;

FIGS. **17** and **18** are fragmentary side elevation of the first example shown in FIG. **16**;

FIG. **19** is a fragmentary front view showing a modification of the first example shown in FIG. **16**;

FIG. **20** is a fragmentary view showing a second example of the third embodiment;

FIG. **21** is a fragmentary front view showing a modification of the second example shown in FIG. **20**;

FIG. **22** is a fragmentary front view showing an image forming cartridge representative of a third example of the third embodiment;

FIGS. **23** and **24** are respectively a perspective view and a front view showing how the inclination of a scanning line is corrected;

FIG. **25**A is a perspective view showing holding means assigned to a mirror;

FIG. **25**B is a fragmentary sectional view of the holding means;

FIG. **26** is a fragmentary front view showing a modification of the third example shown in FIG. **22**;

FIG. **27** is a fragmentary front view showing another modification of the example shown in FIG. **22**;

FIG. **28** is a perspective view showing an apparatus body representative of a fourth example of the third embodiment;

FIG. **29** is a perspective view showing a modification of the fourth example shown in FIG. **28**;

FIG. **30** is a perspective view showing an apparatus body representative of a fifth example of the third embodiment;

FIG. **31** is a perspective view showing a modification of the fifth example shown in FIG. **30**;

FIG. **32** is a fragmentary view showing a sixth example of the third embodiment;

FIG. **33** is a fragmentary front view showing the sixth example shown in FIG. **32**;

FIG. **34**A is a sectional view showing the structure of a writing unit included in a seventh example of the third embodiment and a positional relation between it and photoconductive elements;

FIG. **34**B is a fragmentary sectional view showing a dust-proof glass included in the seventh example shown in FIG. **34**A;

FIG. **35** is a fragmentary plan view showing a ninth example of the third embodiment;

FIG. **36** is a fragmentary front view of the ninth example shown in FIG. **35**;

FIG. **37** is a fragmentary sectional view showing a portion for mounting an optical writing unit included in the ninth example of FIG. **35**;

FIG. **38** is a view similar to FIG. **37**, showing a modification of the portion of FIG. **37**;

FIG. **39** is a perspective view showing how an optical writing unit is mounted in a tenth example of the third embodiment;

FIG. **40** is a fragmentary plan view showing an eleventh example of the third embodiment;

FIG. **41** is a front view of the eleventh example shown in FIG. **40**;

FIG. **42** is a front view showing a twelfth example of the third embodiment;

FIGS. **43**A–**43**D are front views each showing a particular image forming cartridge not including a photoconductive element;

FIG. **44** is a fragmentary front view of a conventional image forming apparatus;

FIG. **45** is an external perspective view of the conventional image forming apparatus;

FIG. **46** is a section along line J—J of FIG. **45**;

FIGS. **47** and **48** are respectively a plan view and a side elevation showing an image forming cartridge included in the conventional apparatus;

FIG. **49** shows the image forming cartridge of the conventional apparatus mounted to an apparatus body;

FIG. **50** is a view showing a spacing member for providing a preselected space between a developing roller and a photoconductive element

FIG. **51** is a front view showing a part of an image forming apparatus of the type having photoconductive elements mounted on its body beforehand;

FIGS. **52**A–**52**D are front views each showing a particular image forming cartridge not including a photoconductive element;

FIG. **53**A is a view showing an image forming cartridge vibrating in the up-and-down direction;

FIG. **53**B is a view similar to FIG. **53**A, showing the cartridge vibrating in the torsional direction;

FIG. **54** is a section along line Q—Q of FIG. **45**;

FIG. **55** is a section along line W—W of FIG. **54**; and

FIGS. **56**A and **56**B are views respectively showing a vertical vibration mode and a torsional vibration mode.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

To better understand the present invention, reference will be made to a conventional image forming apparatus capable of forming a full-color image with a plurality of image forming cartridges, shown in FIGS. **44**–**46**. As shown in FIG. **44**, an image transfer belt (simply belt hereinafter) **1** is passed over rollers **2** and **3** and extends in the up-and-down direction. At the time of image formation, the belt **1** turns in such a direction that its surface for retaining a paper or similar recording medium moves upward, as indicated by an arrow in FIG. **44**.

Four image forming cartridges (simply cartridges hereinafter) **4**, **5**, **6** and **7** are arranged one above the other

and face the above surface of the belt **1** moving upward. The cartridges **4**–**7** are assumed to store black (K) toner, cyan (C) toner, magenta (M) toner and yellow (Y) toner, respectively. The cartridges **4**–**7** are identical in mechanical construction and therefore in members constituting them. Let the following description concentrate on the cartridge **5** by way of example. The other cartridges **4**, **6** and **7** are simply distinguished from the cartridge **5** by suffices Y, M and K attached to the reference numerals.

The cartridge **5** includes a photoconductive element in the form of a drum **8**C and image forming means for forming an image on the drum **8**C. The image forming means includes a charge roller **9**C, a developing roller **100** and a cleaning blade **12**C arranged around the drum **8**C. The charge roller **9**C plays the role of charging means. The developing roller or developing means feeds toner to the drum **8**C. The cleaning blade **12**C removes toner left on the drum **8**C after image transfer.

A supply roller **11**C is associated with the developing roller **10**C for supplying a developer to the roller **10**C. Rotary bodies **13**C and **14**C convey the developer toward the supply roller **11**C while agitating it. Optical writing means **104**C, which will be described later, emits a light beam Lb to an image writing position on the drum **9**C between the charge roller **9**C and the developing roller **10**C.

As shown in FIG. **45**, the cartridges **4**–**7** are removably mounted to an apparatus body **22** for maintenance including the replacement of various image forming members each having a particular life. Specifically, as shown in FIG. **44**, lock pins or positioning and supporting means **16**C and **17**C extend in the direction in which the cartridge **5** is mounted and dismounted, i.e., the direction perpendicular to the sheet surface of FIG. **44**. Further, as shown in FIGS. **46**–**48**, a drive joint or drive inputting means **15**C is provided for transferring a driving force to the above image forming means.

As shown in FIG. **45**, the apparatus body **22** is implemented as a hexahedral box-like frame. Specifically, the apparatus body **22** has a front wall **22***a* through which the cartridge **5** is mounted and dismounted, a rear wall **22***b* facing the front wall **22***a*, a right side wall **22***c*, a left side wall **22***d*, a top wall **22***e*, and a bottom wall **22***f*. While the walls **22***a*–**22***f* are shown as each having a simple configuration, they are in practice provided with notches, bent portions, holes and so forth for mounting various parts.

A wide opening is formed in the front wall **22***a* in the up-and-down direction for receiving the cartridges **4**–**7** in the axial direction of the drums. As shown in FIGS. **47** and **48**, a rectangular window is formed in one side of the cartridge **5**, so that the drum **8**C is partly exposed to the outside through the window. The shaft of the drum **8**C is journal led to the case of the cartridge **5**. The drive joint **15**C mentioned earlier is tapered and mounted on one end of the shaft of the drum **8**C.

As shown in FIG. **49**, holes **16**C' and **17**C' are formed in the front wall **22***a* for receiving the lock pins **16**C and **17**C. As shown in FIGS. **46** and **49**, a prime joint **15**C' is mounted on the rear wall **22***b* and mates with the drive joint **15**C.

To mount the cartridge **5** to the apparatus body **22**, the cartridge **5** is inserted into the apparatus body **22** in the mounting and dismounting direction in FIGS. **45**, **47** and **48**. At the same time as the lock pins **16**C and **17**C mate with the holes **16**C' and **17**C', respectively, the drive joint **15**C mates with the tapered bore of the prime joint **15**C. In this manner, the cartridge **5** is locked to the apparatus body **22** mainly at three points, i.e., by the drive joint **15**C mating with the prime joint **15**C' mounted on the back of the rear wall **22***b* and the lock pins **16**C and **17**C mating with the holes of the front wall **22***a*. The prime joint **15**C' is connected to a drive source not shown. Such a configuration is also applied to the other cartridges **4**, **6** and **7**.

As shown in FIG. **44**, a pair of registration rollers **18** are positioned in the vicinity of the lower end of the belt **1**. In a full-color mode, the cartridges **4**–**7** respectively form toner images on their photoconductive drums in black, cyan, magenta and yellow. A paper or similar recording medium is conveyed by the registration roller **18** toward the top of the belt **1** along an inlet passage indicated by an arrow in FIG. **44**. While the belt **1** conveys the paper upward, a Y, an M, a C and a K toner image are sequentially transferred from the drums of the cartridges **7**–**4** one above the other. The paper with the resulting full-color image is driven out of the apparatus via a fixing device not shown.

Assume that any one of the cartridges **4**–**7** runs out of toner or reaches a time for maintenance. Then, only the cartridge needing maintenance is pulled out of the apparatus body **22**, maintained, and again mounted to the apparatus body **22**, or replaced with a new cartridge.

The cartridge **5**, for example, is removably supported at three points by the lock pins **16**C and **17**C and drive joint **15**C. The charge roller **9**C, developing roller **10**C and so forth each are supported by the cartridge **5** at axially opposite ends thereof. To insure accuracy, the lock pins **16**C and **17**C and drive joints **15**C supporting the cartridge **5** on the apparatus body **22** are positioned on the side walls of the cartridge **5** supporting the opposite ends of the above rollers **9**C and **10**C.

As stated above, the cartridge **5** is supported by the apparatus body **22** at its opposite ends in the lengthwise direction in a so-called bridge structure. As a result, the vibration of the apparatus body **22** ascribable to, e.g., the drive of the belt **1** and paper and the drive of the fixing device causes the cartridge **5** to vibrate.

Basically, the cartridge **5** is caused to vibrate either in the vertical direction, as indicated by an arrow in FIG. **53**A, or in the torsional direction, as indicated by arrows of different directions in FIG. **53**B. Let the vibration modes shown in FIGS. **53**A and **53**B be referred to as a vertical mode and a torsional mode, respectively. When the cartridge **5** bodily vibrates in either one of the above modes, the vibration is directly transferred to the drum **8**C supported by the cartridge **5**. Also, the vibration of the cartridge **5** is transferred to the drum **8**C via the charge roller **9**C, developing roller **10**C, cleaning blade **12**C and other image forming means. As a result, a displacement mainly ascribable to the drum **8**C itself shifts the image writing position and an image transferring position. This makes the scanning pitch irregular in the subscanning direction (the direction of movement of the belt **1**) in accordance with the resonance frequency. The irregular scanning pitch causes the density of an image to be periodically irregular in the subscanning direction (so-called banding). This is also true with the other cartridges **4**, **6** and **7**.

Another conventional type of image forming apparatus has photoconductive drums not mounted on the cartridges, but journal led to its body beforehand. In this type of apparatus, each cartridge includes a developing roller and a toner hopper for feeding toner to the developing roller and is mounted to the apparatus body by members similar to the lock pins and drive joint of FIGS. **46**–**49**. For example, when the C cartridge **5** is mounted to the apparatus body **22**, the developing roller **10**C is brought into contact with the drum **8**C mounted on the apparatus body **22** beforehand.

FIGS. **50**, **51** and **52**B show another specific configuration. As shown, when a C cartridge **5**". is mounted to the apparatus body **22**, a developing roller **10**C" mounted on the cartridge **5**" is spaced from a photoconductive drum **8**C" by a small gap. As shown in FIG. **50**, to maintain the above small gap, rings **10**C"-**1** and **10**C"-**2** are mounted on the axially opposite ends of the developing roller **10**C"; the rings **10**C"-**1** and **10**C"-**2** are greater in diameter than the developing roller **10**C". The drum **8**C" is mounted on the apparatus body **22** beforehand. When the cartridge **5**" is mounted to the apparatus body **22**, the rings **10**C"-**1** and **10**C"-**2** abut against the axially opposite ends of the drum **8**C" and thereby form the above gap.

The above relation also applies to the other cartridges **4**", **6**" and **7**". Specifically, as shown in FIG. **51**, photoconductive drums **8**K", **8**M" and **8**Y" are mounted on the apparatus body **22** beforehand. As shown in FIGS. **52**A, **52**C and **52**D, developing rollers **10**K", **10**M" and **10**Y" each having rings corresponding to the rings **10**C"-**1** and **10**C"-**2** are mounted on the cartridges **4**", **6**" and **7**", respectively. When the cartridges **4**", **6**" and **7**" are mounted to the apparatus body **22**. the developing rollers **10**K", **10**M" and **10**Y" are respectively spaced from the drums **8**K", **8**M" and **8**Y" by the preselected small gap.

In the above apparatus, the developing roller **10**C" journal led to the cartridge or the rings or spacing members **10**C"-**1** and **10**C"**2**-**2** abut against the drum **8**C" mounted on the apparatus body **22** beforehand. Consequently, when the cartridge vibrates, the drum **8**C" vibrates via the developing roller or developing means **10**C" or the rings **10**C"-**1** and **10**C"-**2**. This results in banding in the same manner as with the cartridge **5** including the drum **8**C. Specific cases in which such banding occurs are as follows.

(1) In the apparatus wherein the drum **8**C is mounted on the cartridge **5**, more specifically the case of the cartridge **5**, when the cartridge **5** is mounted to the apparatus body **22** for image formation, the vibration of the cartridge **5** is transferred to the drum **8**C via the charge roller, developing roller **10**C, cleaning blade **12**C and other image forming means, resulting in banding. More specifically, the drum **8**C and developing roller **10**C are supported by a single member (cartridge **5**) and can therefore be accurately spaced from each other without resorting to the rings **10**"-**1** and **10**"-**2**, FIG. **7**. However, the vibration of the cartridge **5** is transferred to the drum **8**C and additionally transferred to the drum **8**C via the charge roller **9**C, cleaning blade **12**C and other image forming means mounted on the cartridge **5**.

(2) As shown in FIGS. **50**–**53**, assume the configuration wherein when the cartridge is mounted to the apparatus body, the developing means (developing roller **10**C" or the rings **10**"C-**1** and **10**"C"-**2**) mounted on the cartridge or one or more of the charging means and cleaning means abut against the drum **8**C" mounted on the apparatus body. Even in this configuration, the vibration of the cartridge is transferred to the drum **8**C" and brings about banding.

In any case, banding ascribable to the vibration of the cartridge is extremely conspicuous at and around a pitch of 0.5 mm, but it is not noticeable when the vibration frequency and therefore the pitch on an image decreases. It follows that when the resonance frequency is low in the previously mentioned modes, banding is conspicuous and often degrades an image to a critical degree. This is particularly true with an image forming apparatus including a plurality of cartridges that are driven by a sophisticated mechanism.

Conventional arrangements for supporting an image forming unit removably mounted to an apparatus body may be generally classified into the following three types:

(a) an arrangement wherein a process cartridge including four developing units arranged side by side and a photoconductive belt is removably mounted to the apparatus body; the process cartridge is supported by a resilient member affixed to a push-up member mounted on the apparatus body (Japanese Patent Laid-Open Publication No. 5-313425)

(b) an arrangement wherein a plurality of toner cartridges are removably mounted to a developing device facing an image carrier; nearby toner cartridges are formed with projections and recesses mating with each other and prevented from shaking thereby (Japanese Patent Laid-Open Publication No. 6-148968); and

(c) an arrangement wherein a toner cartridge for replenishing toner is mounted to a process cartridge including a photoconductive drum and removable from the apparatus body; a guide member restricts the position of the toner cartridge being pushed into toner storing means included in the process cartridge (Japanese Patent Laid-Open Publication No. 10-20647).

Referring again to FIG. **44**, four optical writing means **104**K, **104**C, **104**M and **104**Y are stacked one above the other in the direction of gravity and correspond to the four cartridges **4**, **5**, **6** and **7**, respectively. Because the writing means **104**K–**104**Y are identical in mechanical arrangement and therefore in members constituting them, let the following description concentrate on the writing means **104**C by way of example. The other writing means **104**K, **104**M and **104**Y are simply distinguished from the writing means **14**C by suffixes Y, M and K added to the reference numerals. Also, only the operation of the writing means **104**C and that of the cartridge **5** will be described because the operations of the others will be understood by analogy.

The writing means **104**C scans the drum **8**C with the light beam Lb in order to form a latent image on the drum **8**C. Specifically, in the writing means **10**C, a laser beam issuing from a laser diode, not shown, is steered by a polygonal mirror **106**C and then focused on the drum **8**C in the form of a beam spot via a first f-θ lens **108**C, mirrors **110**C and **111**C, and a second f-θ lens **112**C.

The cartridge **5** includes, in addition to the drum **8**, the cleaning means, charging means, developing means, toner and others necessary for image formation and each having a particular life.

In the above apparatus, the cartridges **4**–**7** are stacked one above the other at intervals, which are too small to position the writing means **104**K–**104**Y therebetween. This is why the writing means **104**K–**104**Y are located at positions relatively remote from the drums **8**K–**8**Y in the horizontal direction.

When the writing means **104**C, for example, vibrates, the beam spot on the drum **8**C is noticeably displaced and apt to bring about banding.

The apparatus body **22** is basically made up of the front wall **22***a*, rear wall **22***b*, side walls **22***c* and **22***d*, top wall **22***e*, and bottom wall **22***f*, as described with reference to FIG. **45**. As shown in FIGS. **54** and **55**, the writing means **104**C is mounted on a flat base member **328**C extending between the front wall **22***a* and the rear wall **22***b*. The base member **328**C is affixed to the rear wall **22***b* at the rear end and supported by the front wall **22***a* via adjusting means **330**C at the front end. The base member **328**C and adjusting means **330**C form a bridge structure.

The adjusting means **330**C is used to move the front end of the base member **328**C upward or downward, i.e., in the

subscanning direction in order to adjust the inclination of the light beam Lb issuing from the writing means **104**C. By so adjusting all the writing means, it is possible to prevent four images of different colors from being inclined by different angles when superposed.

Specifically, as shown in FIG. **54**, the base member **328**C is formed with a slit-like notch **328***a* at its rear end, so that it can be moved in the above direction on a hinge basis. While adjusting means **330**KI, **330**C, **330**M and **330**Y are assigned to all of the different colors, the base member of one writing means assigned to one reference color may be directly affixed to the front wall **22***a* and rear wall **22***b* without the intermediary of the adjusting member. This allows one of such adjusting means to be omitted.

Technologies for adjusting the position of optical writing means or for preventing it from being displaced are also disclosed in Japanese Patent Laid-Open Publication Nos. 5-6071, 7-104545, and 6-34901. In Laid-Open Publication No. 5-6071, optical writing means is adjustably mounted on a structural body via a spring, a screw, etc. In Laid-Open Publication No. 7-104545, a structural body is formed of ceramics or similar material having a small coefficient of thermal expansion in order to obviate the dislocation of colors ascribable to thermal expansion. In Laid-Open Publication No. 6-34901, an elastic member is interposed between the housing of optical writing means and a cover for reducing the vibration of the cover which would effect optical writing.

The cartridges **4**–**7** and optical writing means **104**K-**104**Y arranged one above the other in the direction of gravity, as stated above, promote the miniaturization of the apparatus. However, because the base members **328**K–**328**Y and adjusting means **330**K–**330**Y are provided in a bridge structure, the vertical mode shown in FIG. **56**A and torsional mode shown in FIG. **56**B basically exist with, e.g., the writing means **104**C. This is also true with the other writing means **104**K, **104**M and **104**Y.

Assume that the vibration of, e.g., the drive source is imparted to the writing means **104**C via the front wall **22***c* and rear wall **22***b*, causing the writing means **104**C to bodily vibrate. Then, the beam spot on the drum **8**C is periodically displaced with the result that the scanning pitch in the subscanning direction becomes irregular in accordance with the resonance frequency. The irregular scanning pitch causes the image density to become periodically irregular in the subscanning direction and thereby brings about banding, as discussed earlier.

Banding is more conspicuous with an image forming apparatus including a plurality of optical writing means than with a single-color image forming apparatus. This is because the apparatus with a plurality of optical writing means needs a sophisticated driveline apt to increase-the vibration level, requires each writing means to have a small cross-sectional area for miniaturization which is apt to aggravate vibration, and makes it difficult to arrange a strong structural body around the writing means due to the limited space.

As stated above, banding ascribable to the vibration of the image forming cartridges and that of the optical writing means is the problem with the conventional technologies.

Preferred embodiments of the image forming apparatus in accordance with the present invention will be described hereinafter.

1st Embodiment

Basically, this embodiment constitutes an improvement mainly over the conventional image forming cartridge described with reference to FIGS. **44**–**52**. Briefly, the illustrative embodiment is constructed to obviate banding ascribable to the vibration of the photoconductive elements caused by the vibration of the image forming cartridges. Therefore, the embodiment is applicable to both of the construction wherein the photoconductive elements are mounted on the cartridges, more particularly the cases of the cartridges, and the construction wherein when the cartridges supporting the photoconductive elements are mounted to the apparatus body, one or more of the charge rollers, developing means with the developing rollers or the spacing members, and cleaning blades abut against the associated photoconductive elements.

The following description will concentrate on the construction described with reference to FIGS. **44**–**49** and **53**, i.e., the apparatus of the type including the photoconductive elements mounted on the cartridges. However, the illustrative embodiment is similarly applicable to the apparatus described with reference to FIGS. **50**–**52** wherein the photoconductive elements are mounted on the apparatus body.

EXAMPLE 1

FIGS. **1**A and **1**B show a first example of the first embodiment. To reduce the size of an image forming apparatus, it is preferable to stack a plurality of image forming cartridges one above the other in the direction of gravity at a small distance or pitch. In this example, structural members (horizontal stays hereinafter) **25** each are interposed between nearby ones of a plurality of cartridges **4**–**7** arranged at a small pitch. Horizontal stays **25** similar to the above stays **25** are also positioned above the top cartridge **4** and below the bottom cartridge **7**, respectively.

The horizontal stays **25** each are implemented as a plate bent upward at its opposite ends in the direction perpendicular to the cartridge mounting and dismounting direction. The stays **25** are affixed to the front wall **22***a* in the vicinity of the cartridge mounting and dismounting opening and the rear wall **22***b* by fastening means not shown.

The cartridges **4**–**7** each are supported by the upper surface of the associated stay **25**. Because the stays **25** are fastened to the front wall **22***a* in the vicinity of the opening and the rear wall **22***b*, as stated above, the two walls **22** and **22***b* are connected together by the stays **25** in the vicinity of the cartridges **4**–**7**.

As for the cartridge **5**, the vibration of the lock pins **16**C and **17**C and drive joint **15**C can be effectively reduced because they rest on the front wall **22***a* and rear wall **22***b*. This is also true with the other cartridges **4**, **6** and **7**. Particularly, as for a vibration mode in which the front wall **22***a* and rear wall **22***b* perform planar vibration, the stays **25** are configured to just halve the plane. This successfully obviates a low frequency resonance mode undesirable from the banding standpoint and thereby allows only a high frequency resonance mode to occur. In addition, the stays **25** positioned above the top cartridge **4** and below the bottom cartridge **7** increase the rigidity of the entire cartridge support structure and thereby further promote the obviation of banding.

The stays **25** may be formed with holes and notches for implementing cooling passages and for an assembly purpose so long as they do not reduce strength. At the opening for mounting and dismounting the cartridges, the edges of the stay **25** are exposed to the outside and should preferably be bent or folded for safety and greater strength.

The cartridges **4**–**7** have substantially the same sectional shape and extend in the axial direction of, e.g., the photoconductive drums **8**K–**8**Y. Therefore, so long as the car-

tridges **4**–**7** are mounted and dismounted in the axial direction of the drums **8**K–**8**Y, as in this example, the stays **25** may be formed with projections and recesses complementary to the sectional shape of the cartridges **4**–**7**. Such projections and recesses increase the strength of the structural body and save space without interfering with the cartridges **4**–**7** at the time of mounting or dismounting.

Further, the cartridges **4**–**7** each storing a developer of particular color are identical in mechanical arrangement and can therefore be produced with identical specifications. This promotes the efficient production of the cartridges **4**–**7** on a quantity basis.

Preferably, the members needing accurate positioning relative to the apparatus body **22**, e.g., the drums **8**Y–**8**K have their shafts supported by bearings with play (margin) relative to the associated cartridges in the direction perpendicular to the shafts. Then, the cartridges each are positioned on a preselected part of the associated stay **25**. In this configuration, when each cartridge is affixed to the apparatus body **22**, the shaft of the drum mounted on the cartridge with the above play moves within the range of the play. As a result, the drive joint **15**C, FIG. **49**, mates with the prime joint **15**C mounted on the apparatus body **22**, setting up a drive transmission path.

As stated above, each photoconductive drum is supported by the associated cartridge in, so to speak, a floating manner. Therefore, when the cartridge is positioned relative to the apparatus body **22** via the associated stay **25**, the drive joint mounted on the shaft of the drum is brought into engagement with the prime joint. As a result, the drum is accurately positioned on the apparatus body **22**. Further, the cartridge does not need a support structure for accurately positioning the drum relative to the cartridge. In addition, the cartridge supported by the stay **25** vibrates little. That is, both of the accurate positioning of the drum relative to the apparatus body **20** and the reduction of vibration of the cartridge are achievable at the same time. Because a plurality of stays **25** are arranged one above the other in association with the cartridges, there can be effectively suppressed vibration in the vertical direction and therefore banding.

EXAMPLE 2

FIGS. **2**A and **2**B show a second example of the first embodiment. As shown, the bottom of, e.g., the cartridge **5** is curved in the form of a letter W complementarily to the curvatures of nearby rotary bodies **13**C and **14**C. The boundary between the two downwardly convex curved portions is implemented as a recess **26**C extending in the mounting and dismounting direction of the cartridge **5**.

In this example, a guide **27**C implemented as a flat plate stands upright from the upper surface of each horizontal stay **25** of Example 1 and is received in the recess or portion to be guided **26**C of the cartridge **5** above the stay **25**. In this condition, the guide **27**C guides the cartridge **5**. The other cartridges are also provided with such guides **27**C. The stay **25** above the top cartridge **4** is not provided with the guide **27**C because it has nothing to guide.

The guide **27**C received in and extending along the recess **26**C of the cartridge positioned above the guide **27**C prevents the cartridge being mounted to or dismounted from the apparatus body **2** from being displaced in the direction perpendicular to the mounting or dismounting direction or from being rotated to hit against the surrounding members.

As shown in FIG. **2**B, the guide **27**C. as well as guides **27**K, **27**M and **27**Y, is increased in height halfway. This configuration is successful to reduce the clearance between the guide and the portion to be guided at the last stage of mounting and therefore to guide the cartridge with accuracy.

The guides **27**K–**27**Y may be respectively molded integrally with the stays **25** or may be produced independently of the stays **25** and then affixed to the stays **25**. Moreover, the upright guides **27**K–**27**Y increase the bending rigidity of the stays **25** in the up-and-down direction and thereby increase mechanical strength and obviates banding.

EXAMPLE 3

FIGS. **3**A and **3**B show a third example of the illustrative embodiment. As shown, among the stays included in Example 1, the stay **25** between the cartridges **4** and **5**, the stay **25** between the cartridges **5** and **6** and the stay **25** between the cartridges **6** and **7** each are provided with resilient pressing means for pressing the overlying and underlying cartridges.

Specifically, as shown in FIGS. **3**A, **3**B and **6**, the pressing means is implemented by leaf springs **28**U and **28**D each having a flat portion **28***a* and a curved portion **28***b*. The leaf spring **28**U has its flat portion **28***a* affixed to the upper surface of the stay **25** with the curved portion **28***b* being convex upward. The leaf spring **28**D has its flat portion **28***a* affixed to the lower surface of the stay **25** with the curved portion **28***b* being convex downward.

The leaf springs **28**U and **28**D are respectively affixed to the intermediate portion of the upper surface and the intermediate portion of the lower surface of the stay **25**. The leaf spring **28**U resiliently presses the cartridge **4** overlying the stay **25** upward while the leaf spring **28**D resiliently presses the cartridge **5** underlying the stay **25** downward. Paying attention to the leaf springs **28**U and **28**D on the stay **25** intervening between the cartridges **4** and **5**, the curved portion **28***b* of the spring **28**U presses the cartridge **4** upward while the curved portion **28***b* of the spring **280** presses the cartridge **5** downward. This is also true with the leaf springs **28**U and **28**D affixed to the stay **25** between the cartridges **5** and **6** and the stay **25** between the cartridges **6** and **7**. The leaf springs **28**U and **28**D resiliently support the antinode portions of the cartridges **4**–**7** as to the amplitude of vibration and thereby effectively suppress vibration.

Assume that the guides **27**K–**27**Y shown in FIGS. **2**A and **2**B are applied to this example. Then, the leaf springs **28**U are so positioned as to respectively contact the two convex portions of the bottom of the overlying cartridge, so that the springs **28**U do not interfere with the above guide. This configuration will be described specifically later with reference to FIG. **4**A.

The leaf springs **28**U and **28**D pressing the bottom of the overlying cartridge and the top of the underlying cartridge, respectively. may be positioned face-to-face and provided with the same resilient force. This arrangement is advantageous in that the resilient forces of the leaf springs **28**U and **28**D cancel each other and do not bend the entire cartridges. Such leaf springs or similar biasing parts may also be provided above the top cartridge and below the bottom cartridge for the same purpose.

Each cartridge may be formed with recesses such that the leaf springs **28**U and **28**D click into the recesses when the cartridge is inserted into the apparatus body **22** as far as a preselected position. The clicking action of the leaf springs **28**Y and **28**D will allow the operator to surely feel the insertion of the cartridge.

Further, the above recesses for the clicking action may be configured to more firmly mate with the leaf springs **28**U and **28**D. This allows the cartridges to be fixed in place

without resorting to lock levers or similar extra affixing means and thereby reduces the cost of the apparatus. This example may be combined with the guides of Example 2 in order to promote easy mounting and dismounting of the cartridges. The leaf springs **28**U and **28**D may be replaced with any other suitable resilient members, if desired.

EXAMPLE 4

FIGS. **4**A and **4**B show a fourth example of the illustrative embodiment. As shown, a vibration-proof rubber block **29** is fitted on the lower surface of the stay **25** overlying the cartridge **4**. The rubber block **29** contacts the upper surface of the cartridge **4** and exerts a viscoelastic pressing force between the stay **25** and the cartridge **4**. Such rubber blocks **29** are also fitted on the lower surfaces of the stays **25** overlying the other cartridges **5**, **6** and **7**, respectively. As shown in FIG. **7**, each rubber block **29** has a rectangular configuration.

Two leaf springs **28**U each having the configuration shown in FIG. **6** are affixed to the upper surface of the stay **25** between the cartridges **4** and **5** at positions around a position facing the rubber block **29**. The leaf springs **28**U are also affixed to the upper surface of the stay **25** between the cartridges **5** and **6** and the upper surface of the stay **25** between the cartridges **6** and **7** in exactly the same manner as the above leaf springs **28**U.

As shown in FIG. **4**A, at the position facing the rubber block **29**, the bottom of the casing of the cartridge is recessed. The two leaf springs **28**Y are respectively positioned to face the two convex portions of the casing on both sides of the above recess. The leaf springs **28**U and rubber block **29** constitute vibration proofing means.

The leaf springs **28**U bias the overlying cartridge upward. The cartridge is therefore pressed against the overlying rubber block **29** with the result that the rubber block **29** exerts a viscoelastic force on the cartridge. The rubber block **29** enhances vibration proofing based on the thermal conversion of vibration energy making the most of the viscoelastic characteristic.

In this example, even leaf springs exerting a relatively small resilient force can implement the above vibration proofing, so that the force to at on each cartridge is reduced. That is, this example causes a minimum of deformation to occur despite the use of the leaf springs and is therefore desirable from the accuracy standpoint as well.

With the combination of the leaf springs and rubber blocks, it is possible to effectively generate the force for pressing each cartridge against the overlaying rubber block. Further, by additionally using the guide arrangement of Example 2 and so configuring the guide as to increase the frictional force of the rubber block **29** just before the completion of the insertion of the cartridge, it is possible to reduce the manual force required to slide the cartridge on the rubber block **29** to an adequate degree.

EXAMPLE 5

FIGS. **5**A and **5**B show a fifth example of the illustrative embodiment. As shown in FIGS. **5**A and **8**, a flat vertical stay **30** is mounted on the left ends of the stays **25** and faces the left side wall **22***d* (FIG. **45**). As shown in FIG. **8**, the vertical stay **30** includes mounting portions **30***b* positioned to face the scanning direction of the light beams Lb. The mounting portions **30***b* are affixed to the front wall **22***a* and rear wall **22***b*, respectively. The stay **30** is affixed to the top wall **22***e* at its upper end and affixed to the bottom wall **22***f* at its lower end. The vertical flat portion of the stay **30** is fastened to the horizontal stays **25** by screws **210**.

In the above configuration, the horizontal stays **25** are firmly affixed to the apparatus body via the vertical stay **30** and reduce the planar vibration mode of the front wall **22***a* and rear wall **22***b* more positively. In addition, the stays **25** and stay **30** substantially perpendicular to each other realize an extremely great sectional moment and thereby provides the structural body with great bending rigidity.

Particularly, the improved bending rigidity is successful to reduce the vibration of the horizontal stays **25** themselves in the event of suppression of vibration, as described in relation to Examples 3 and 4. This example may therefore be combined with the configurations of Examples 3 and 4.

Optical writing devices, not shown, are located at the left-hand side of the cartridges **4**–**7** shown in FIG. **5**A and respectively emit the light beams Lb toward the drums **8**K–**8**Y. The writing devices may also be supported by a structural body similar to the structural body including the vertical stay **30**. In such a case, the stay **30** bears a compression stress (buckling load) ascribable to the weights of the cartridges and those of the writing devices in the vertical direction. This condition increases strength, reduces deformation and suppresses resonance more positively than a condition wherein the cartridges and writing devices are arranged on horizontal plates. This will be described more specifically in conjunction with Example 1 of 3rd Embodiment.

As shown in FIG. **8**, the vertical stay **30** is formed with slots **30***d* each extending in the scanning direction of the light beam Lb with a width corresponding to the diameter of the light beam Lb. The light beams Lb issuing from the writing devices are respectively passed through the slots **30***d*. That is, each slot **30***d* has a minimum necessary length and a minimum necessary width for allowing the light beam Lb to pass therethrough. This minimizes a decrease in the rigidity of the stay **30** as a structural body and serves to obviate banding.

The vertical stay **30** may be additionally formed with holes and notches so long as they do not reduce the strength of the stay **30**. For example, as shown in FIG. **8**, holes **30***c* positioned above and below each slot **30***d* are used to affix the horizontal stays **20** to the vertical stay **30**. It should be noted that any suitable number of holes **30***c* may be formed in the stay **30**. While the stays **20** are fastened to the stay **30** by the screws **210**, the screws **210** will be replaced with, e.g., soldering when use is made of metal or replaced with, e.g., injection molding when use is made of resin.

Examples 1–5 shown and described may be suitably combined not only to obviate banding but also to promote easy operation and reduce the cost.

2nd Embodiment

This embodiment mainly constitutes an improvement over the construct ion of the conventional optical writing means described with reference to FIGS. **54** and **55**. The structural parts of this embodiment identical with the structural parts of the conventional arrangement are designated by like reference numerals and will not be described specifically in order to avoid redundancy.

EXAMPLE 1

As shown in FIGS. **9**–**11**, this example is implemented as a full-color image forming apparatus including four image forming cartridges **4**–**7** stacked one above the other in the

direction of gravity. Four optical writing means **104**K–**104**Y are also arranged one above the other in the direction of gravity and associated with the cartridges **4**–**7**, respectively. The writing means **104**K–**104**Y respectively include the adjusting means **330**K–**330**Y stated earlier.

As shown in FIG. **11**, a flat structural member **202** is positioned between nearby ones of the writing means **104**K–**104**Y, i.e., between the base member **328**K and the writing means **104**C underlying the base member **328**K. The structural member **202** partitions off the space between the nearby writing means. The structural member **202** is affixed to the front wall **22***a* and rear wall **22***b* by fastening means, not shown, at opposite ends thereof.

Structural members **202** are also provided between the writing means **104**C and **104**M and between the writing means **104**M and **104**Y in exactly the same manner as the above structural member **202**. In FIG. **9**, the base members **328**K–**328**Y included in the writing means **104**K–**104**Y are not shown.

The structural members **202** between the consecutive writing means **104**K–**104**Y increase the structural strength of the front wall **22***a* and rear wall **22***b*, among others. This is successful to suppress the vibration of the portions around the positions where the writing means **104**K–**104**Y are affixed to the walls **22***a* and **22***b*. Particularly, as for the planar vibration mode of the walls **22** and **22***b*, the structural members **202** divide the plane of vibration and eliminates a low frequency resonance mode apt to result in banding.

As shown in FIG. **11**, the structural members **202** represented by dash-and-dot lines P1 and P2 may also be positioned above the top writing means **104**K and below the bottom writing means **104**Y. Such structural members **202** further increase the total strength of the apparatus body and enhance the anti-banding function.

The structural members **202** may be formed with holes and notches for cooling and mounting purposes so long as they do not reduce the strength implementing the above anti-banding function. Further, the structural members **202** may be suitably bent or folded. The cartridges **4**–**7** and writing means **104**K–**104**Y should preferably be arranged at a small pitch in order to further miniaturize the apparatus.

EXAMPLE 2

As shown in FIGS. **6**, **12** and **3**, a leaf spring or pressing means **280**D is mounted on the lower surface of, e.g., the structural member **202** between the writing means **104**C and **104**M for pressing the writing means **104**M downward. Likewise, a leaf spring or pressing means **280**U is mounted on the upper surface of the structural member **202** for pressing the writing means **104**C upward. This configuration is also applied to the other structural members **202**.

The leaf springs **280**U and **280**D are identical in shape and material with the leaf springs **28**U and **28**D described with reference to FIG. **6**. The leaf springs **280**U and **280**D are affixed to the intermediate portion of the upper surface and the intermediate portion of the lower surface of the structural body **202**. In FIG. **13**, the curved portion **28***b* of the leaf spring **280**U and the curved portion **28***b* of the leaf spring **280**D are shown as having different curvatures. This stems from a difference in the distance to the base member of the structural body **202** or distance to the optical writing means. In FIG. **12**, the base members **328**K–**328**Y are not shown. In this manner, the leaf springs **280**U and **280**D each resiliently press associated one of the writing means **104**K–**104**Y upward or downward.

The writing means **104**C, for example, is expected to be displaced by the adjusting means **330** together with the base member **328**C (movable member) and cannot therefore be directly affixed to the structural member **202**. This is also true with the other writing means **104**K, **104**M and **104**Y.

The leaf springs or pressing means **280**U and **280**D allow the structural members **202** to support the writing means **104**C while maintaining the writing means **104**C movable. Assume the vibration mode of FIG. **56**A having nodes at opposite ends of the writing means **104**C and an antinode at the intermediate portion of the writing means **104**C. Then, the leaf springs **280**U and **280**D exert forces in such a manner as to suppress the antinode of the amplitude of the above vibration mode. This further enhances the anti-vibration function available with the structural members **202**. This is also true with the other writing means **104**K, **104**M and **104**Y.

The leaf springs **280**U and **280**D may advantageously exert the same pressing force, so that the resilient forces acting on the top and bottom of each writing means can cancel each other. This prevents the writing means from being bent.

In this example, the leaf springs **280**U and **280**D are also positioned on the upper surface of the top structural members **202** and the lower surface of the bottom structural members **202**, respectively. Although these leaf springs **280**U and **280**D do not actually exhibit their pressing function, they are significant for the following reasons. The structural members **202** all having the leaf springs **280**U and **280**D promote standardization, i.e., general-purpose application and can readily cope with an increase in the number of writing means. Further, the top and bottom structural members **202** increase the mechanical strength of the entire structural body. The leaf springs **280**U and **280**D are a specific form of pressing means and may be replaced with any other suitable resilient means.

EXAMPLE 3

FIGS. **7**, **14** and **15** show a third example of the illustrative embodiment. As shown, a vibration-proof rubber block **29**D is fitted on the lower surface of the structural member **202** between the writing means **104**C and **104**M. Likewise, a vibration-proof rubber block **29**U is fitted on the upper surface of the above structural member **202**. This is also true with the other structural members.

The rubber blocks or vibration proofing means **29**U and **29**D are identical in shape and material with the rubber blocks **29** of FIG. **7** having a viscoelastic characteristic. The rubber blocks **29**U and **29**D each having a suitable size are respectively adhered to the intermediate portion of the upper surface and the intermediate portion of the lower surface of the structural member **202**. In FIG. **14**, the base members **328**K–**328**Y are not shown. The vibration proofing means implemented by the rubber blocks **29**U and **29**D proof vibration based on the thermal conversion of vibration energy and thereby effectively suppress the previously stated vibration mode.

The rubber blocks or vibration proofing means **29**U and **29**D are capable exhibiting their effect based on viscosity even when their elasticity is low, compared to the leaf springs or resilient pressing means **280**U and **280**D. Therefore, the forces to act on the writing means **104**K–**104**Y and therefore the deformation of the writing means **104**K–**104**Y can be reduced, insuring the accuracy of the structural body.

The rubber blocks **29**U and **29**D are also fitted on the upper surface of the top structural member **202** and the lower surface of the bottom structural member **202**, respectively, for the reasons described with reference to FIGS. **6**, **12** and **13**.

The rubber blocks **29**U and **29**D may abut against the base members **328**K–**328**Y or the writing means **104**K–**104**Y via leaf springs or similar resilient members, if desired. In this case, the adjusting means **130**K–**130**Y can function without resorting to the great deformation of the rubber blocks **29**U and **29**D.

EXAMPLE 4

FIGS. **8**, **16** and **17** show a fourth example of the illustrative embodiment. As shown in FIG. **16**, each structural member **202** has vertical walls **202***a* and **202***b* at its right and left edges. The left vertical wall **202***a* is affixed to the left side wall **22***b* by fastening means. The right vertical wall **202***b* is directly affixed to a vertical stray or structural member **300** extending in parallel to the direction of arrangement of a plurality of optical writing means and substantially perpendicularly to each structural member **202**.

The vertical stay **300** may be provided with the same shape and same size as the vertical stay **30** shown in FIG. **8**. The various portions of the stay **300** are designated by the same reference numerals as the portions of the stay **30**. Specifically, the stay **300** includes the portions **30***a* to be affixed to the top wall **22***e* and bottom wall **22***f*, portions **30***b* to be affixed to the front wall **22***a* and rear wall **22***b*, and holes **30***c* for affixing the stay **30** to the structural members **202**. In addition, four slots **30***d* are formed in the stay **300** in order to al low the light beams Lb issuing from the writing means **104**K–**104**Y to pass therethrough.

As shown in FIG. **17**, the right wall **202***b* of each structural member **202** is formed with screw holes **202***c* corresponding in position to the holes **30***c* of the stay **300**. Each structural member **202** and stay **300** are fastened together by screws or fastening means **210**' shown in FIG. **8**.

The stay **300** further promotes the suppression of the planar vibration mode achievable with the front wall **22***a* and rear wall **22***b*. Further, the horizontal structural members **202** and stay **300** substantially perpendicular to each other implement an extremely great sectional moment and provide the structural body with great bending rigidity.

In this example, the writing means **104**K–**10**Y are arranged one above the other in the direction of gravity. The stay **300** therefore bears a compression force ascribable to its own weight and the weights of the structural members **202** in the direction perpendicular to the direction of thickness. Such an arrangement therefore increases strength, reduces deformation and obviates the resonance mode, compared to an arrangement wherein writing means are arranged in the horizontal direction.

The stay **300** formed with the slots **30***d* may be additionally formed with holes and notches for cooling and mounting purposes so long as they do not reduce strength. While the structural members **202** and stay **300** are shown as being connected together by the screws **210**, they may be, e.g., welded together when use is made of metal or may be implemented by a single molding by injection molding.

3rd Embodiment

This embodiment obviates banding by using all or part of the configurations of the examples of the foregoing embodiments.

EXAMPLE 1

In Example 5 of 1st Embodiment shown in FIGS. **5**A, **5**B and **8**, the horizontal stays **25** are connected to the vertical stay **30**. In Example 4 of 2nd Embodiment shown in FIGS. **8** and **17**, the structural members **202** are connected to the vertical stay **300**. The vertical stays **30** and **300** have been shown and described as being separate members having the same shape and same size.

In this example, the vertical stays **30** and **300** shown in FIGS. **5**A and **5**B and FIG. **16**, respectively, are implemented as a single member. Specifically, as shown in FIGS. **18** and **19**, this example includes a single vertical stay **30** to which both the horizontal stays **25** and structural members **202** are connected. In this sense, the vertical stay **30** plays the role of a shared structural member.

In the above configuration, the horizontal stays **25**, vertical stay **30**, structural members **202** and apparatus body **22** are constructed into a single structural body. This increases the rigidity of the entire structure and thereby obviates banding. In addition, the stay **30** serves to reinforce the structural members **202** and horizontal stays **25** and thereby enhances simplification and miniaturization.

In FIG. **19**, the left ends of the structural members **202** are spaced from the left side wall **22***d* for the layout reason. That is, the space is used to accommodate electrical parts and other parts for image formation. Even this configuration is capable of obviating banding because the structural members **202** are affixed to the front wall **22***a* and rear wall **22***b* at their front and rear ends. As shown in FIG. **18**, the left ends of the structural members **202** may be affixed to the left side wall **22***d*, depending on the layout. In FIG. **19**, the horizontal stays **25**, vertical stay **30** and structural members **202** are indicated by bold lines to show that they constitute a single structural body.

EXAMPLE 2

In FIG. **1**, the cartridges **4**–**7** are separated from each other by the structural members or partitions **25**. In the example to be described, the image forming means is received in a casing separate from the image forming cartridge. The casing plays the role of the structural member separating nearby cartridges.

Specifically, as shown in FIG. **20**, casings **35** indicated by bold lines each accommodate the respective image forming means. In this example, as for the cartridge **4**, the developing roller **10**K, supply roller **11**K and rotary bodies **13**K and **14**K are the image forming means received in the casing **35**. On the other hand, the charge roller **9**K and cleaning blade **12**K are mounted on the cartridge **4** as the other image forming means. Because the developing roller **10**K, supply roller **11**K and rotary bodies **13**K and **14**K are positioned below the charge roller **9**K and cleaning blade **12**K, the casing **35** effectively separates the cartridges **4** and **5** from each other. This is also true with the other cartridges **6** and **7**.

Because the charge roller **9**K and cleaning blade **12**K include parts that should be replaced at relatively short intervals, they are constructed into the cartridge **4** removable from the apparatus body **22**. By contrast, the developing roller **10**K, supply roller **11**K and rotary bodies **13**K and **14**K withstand repeated use over a relatively long period of time. These members **10**K, **11**K, **13**K and **14**K can therefore be fixedly connected to the apparatus body **22** only if means for replenishing toner from the outside is provided. This is true with the casings **35** associated with the other cartridges **5**, **6** and **7**. By using the casing **35** as partitions, it is possible to reinforce the structural body and prevent the cartridges **4**–**7** from vibrating.

The casings **35** each have a roll-like configuration surrounding the developing means, e.g., the developing roller **10**K, supply roller **11**K and rotary bodies **13**K and **14**K.

Each casing **35** extends in the front-and-rear direction and has its front end and rear end affixed to the front wall **22***a* and rear wall **22***b,* respectively. The casings **35** are therefore implemented as a single structural body together with the apparatus body. Such a structural body has sufficient strength and prevents the cartridges **4**–**7** from vibrating more positively.

The casings **35** intervening between the cartridges **4**–**7** not only separate the cartridges **4**–**7** from each other, but also serve as casings surrounding the image forming means. This configuration further enhances the simple and miniature construction while obviating banding, compared to the configuration using the structural members **25** for partition.

FIG. **21** shows a modification of the above example. As shown, each casing **35** has an extension **35**a affixed to the vertical stay **30** shown in FIGS. **5**A, **5**B and **19**. This modification further increases the strength of the structural body.

While the casings **35** each accommodate the respective developing means, they may accommodate any other suitable image forming means.

EXAMPLE 3

In the examples shown in FIGS. **9**–**18**, the optical writing means **10**K–**104**Y are respectively provided with the adjusting means **330**K–**330**Y for correcting the shift of scanning lines. The adjusting means **330**K–**330**Y each are positioned outside of the respective housing accommodating the writing means and operated to move the housing. The problem with this configuration is that the housings themselves cannot be used as the structural members **202**. A third example to be described accommodates each adjusting means in the housing so as to use the housing as the structural member **202**. Let the writing means each including the respective adjusting means and accommodated in the respective housing be labeled **104**K', **104**C', **104**M' and **104**Y'. Because the writing means **104**K'–**104**Y' are identical in construction, the following description will concentrate on the writing.means **104**K' by way of example.

As shown in FIG. **22**, the housing of the writing means **104**K' accommodates the polygonal mirror **106**K, first f-θ lens **108**K and mirrors **110**K and **111**K, as stated earlier. As shown in FIGS. **23** and **24**, one end **37** of the mirror **111**K in the lengthwise direction corresponding to the main scanning direction of the light beam Lb is movable by any desired angle about the other end **36**. When the mirror **111**K is so moved, the scanning line formed by the light beam Lb on the drum **8**K is shifted in the subscanning direction at a position corresponding to the above end **37** of the mirror **111**K; the entire scanning line is inclined by, e.g., an angle e. Holding means that will be described holds the mirror **111**K at such an adjusted position. The holding means constitutes the adjusting means.

As shown in FIG. **25**A, one surface of the mirror **111**K is supported by a knife edge **38** in the vicinity of the end **36** in such a manner as to be movable while maintaining a beam reflection angle. The above surface is constantly biased by a compression spring or resilient means **40** in the vicinity of the other end **37**. The other surface of the mirror **111**K is pressed by a moving member **41**. As shown in FIG. **25**, the moving member **41** is a kind of a nut and held in threaded engagement with a screw **43** rotatable coaxially with the output shaft of a motor **42**. A groove **45** is formed in the side of the moving member **41** and elongate in the axial direction of the member **41**. A detent **44** is received in the groove **45**.

The knife edge **38**, spring **40**, moving member **41**, motor **42**, screw **43** and detent **44** constitute the holding means mentioned earlier and playing the role of the adjusting means. When the motor **42** is driven, the mirror **111**K is angularly moved about the knife edge **38** and then locked at the adjusted position.

The above adjusting means associated with the mirror **111**K can be received in the housing of the writing means **104**K'. Therefore, the housing of the writing means **104**K' can be bodily mounted to the apparatus body **22** in a static condition and can therefore replace the structural member **202** for partition.

FIG. **26** shows the writing means **104**K'–**104**H' each having the adjusting means arranged in the respective housing. As shown, the housings each have a bottom plate **47** having a greater size or grater rigidity than the usual bottom plate and connected to the front wall **22***a* and rear wall **22***b* at opposite ends. With this configuration, this example realizes a structure simpler and smaller than the structures of the examples shown in FIGS. **9**–**19**.

As shown in FIG. **27**, the bottom plates **47** of the writing means **104**K'–**104**Y' may be connected to the vertical stay **300** in the same manner as in FIGS. **8** and **16**. The stay **300** is connected to the top wall **22***e* at the upper end, connected to the bottom wall **22***f* at the lower end, connected to the front wall **22***a* at the front end, and connected to the rear wall **22***b* at the rear end. If desired, the structural members **25** shown in FIG. **18** may also be connected to the stay **300**.

EXAMPLE 4

FIG. **28** shows a fourth example of the illustrative embodiment using the horizontal stays **25** described with reference to FIGS. **1**A–**6**. As shown, the apparatus body or frame **22** has the front wall **22***a,* rear wall **22***b,* right side wall **22***c,* left side wall **22***d,* top wall **22***e,* and bottom wall **22***f.* The stays **25** are arranged one above the other in the apparatus body **22** for separating the cartridges **4**–**7**. The drums **8**K–**8**Y included in the cartridges **4**–**7**, respectively, extend perpendicularly to the front wall **22***a.* A single opening **50** is formed in the front wall **22***a* and broad enough to accommodate the cartridges **4**–**7**, so that the cartridges **4**–**7** can be mounted and dismounted in the axial direction of the drums **8**K–**8**Y. The front ends of the stays **25** are affixed to the edges of the opening **50** by screws or fastening means **51** while traversing the opening **50** in the right-and-left direction.

The stays **25** traversing the opening **50** of the front wall **22***a* reinforce the front wall **22***a*. This prevents the rigidity of the front wall **22***a* and therefore the rigidity of the entire frame from decreasing and thereby obviates banding.

FIG. **29** shows a modification of the above example. As shown, the front wall **22***a* of the frame is formed with openings **54**, **55**, **56** and **57** in place of the single opening **50** of FIG. **29**. The openings **54**–**57** are assigned to the cartridges **4**–**7**, respectively. Part of the front wall **22***a* are left in the form of ribs between the openings **54**–**57**, as illustrated. The front ends of the stays **25** are respectively affixed to the ribs by the screws **51**. The rigidity of such a front wall **22***a* decreases little because each opening is small and because a rib intervene between nearby openings, compared to the front wall **22***a* shown in FIG. **28**. This, coupled with the fact that the stays **25** reinforce the front wall **22***a,* insures the rigidity of the frame and obviates banding more positively.

EXAMPLE 5

FIG. **30** shows a fifth example of the illustrative embodiment also using the horizontal stays **25** described with

reference to FIGS. **1A–6**. As shown, the stays **25** for separating the cartridges **4–7** are arranged one above the other in the frame also made up of the six walls **22***a*–**22***f*. The right side wall **22***c* extends perpendicular to the axial direction of the drums **8**K–**8**Y in a horizontal plane. The transfer belt **1** shown in FIG. **9** is disposed in the side wall **22***c*. The entire side wall **22***c* is implemented as a cover **58** surrounding the belt **1** and openable away from the frame.

Specifically, the lower end of the cover **58** is connected to the bottom wall **22***f* by a hinge or a shaft. As shown in FIG. **30**, when the cover **58** is opened away from the frame, the entire area corresponding to the side wall **22***c* is uncovered and allows the cartridges **4–7** to be easily mounted and dismounted therethrough. FIG. **30** shows the cartridge **4** pulled out of the frame.

FIG. **31** shows a modification of the above example. In the foregoing examples, the writing means **104**K–**104**Y or **104**K'–**104**Y' and vertical stay **30** or **300** are arranged at the left-hand side of the cartridges **4–7**, so that the cartridges **4–7** cannot be mounted or dismounted via the position where the left side wall **22***d* is present. The modification of FIG. **31** is constructed to allow the cartridges **4–7** to be mounted and dismounted via the above position.

Specifically, in the modification, a single optical writing unit **100** in the form of a flat box is substituted for the writing means **104**K–**104**Y or **104**K'–**104**Y'. The writing unit **100** is arranged in a cover **59** mainly constituted by the left side wall **22***ds*. The cover **59** is openable away from the frame about a shaft **60**. When the cover **59** is opened, as indicated by a dash-and-dots line in FIG. **31**. it uncovers the area corresponding to the left side wall **22***d* and allows the cartridges **4–7** to be easily mounted and dismounted.

In any case, the side wall of the frame extending perpendicularly to the axial direction of the drums in a horizontal plane is bodily implemented as an openable cover. It is therefore not necessary to form the front wall **22***a* with an opening or openings (FIG. **28** or **29**) which would reduce the rigidity of the structural body and result in banding.

EXAMPLE 6

This example, like the above example, includes the box-like writing unit **100**. As shown in FIGS. **32** and **33**, the writing unit **100** is affixed to a structural body **102** which is affixed to the front wall **22***a* and rear wall **22***b* at its opposite ends. The cartridges **4–7** are stacked one above the other and affixed to the apparatus body **22**.

The writing unit **100** is formed with openings **100**K, **100**C, **100**M and **100**Y respectively aligning with the drums **8**K–**8**Y of the cartridges **4–7** for passing the light beams Lb therethrough. The writing unit **100** is located at a preselected distance from the drums **8**K–**8**Y.

The single writing unit **100** is easier to position than the four writing means **104**K–**104**Y shown in FIG. **9** and reduces the overall size of the apparatus. Further, the single writing unit **100** allows reinforcing members to be easily added for increasing rigidity. In addition, the flat writing unit **100** reduces the space to be occupied to the apparatus.

EXAMPLE 7

FIGS. **34**A and **34**B show a seventh example of the illustrative embodiment and relating to the configuration of the writing unit **100** described with reference to FIGS. **31–33**. As shown in FIG. **34**A, a polygonal mirror **70** is positioned at the center of the writing unit **100** and constitutes a polygon scanner. A motor **72** causes the polygonal mirror **70** to rotate. The mirror **70** has an axis of rotation extending perpendicularly to the axial direction of the drums **8**K–**8**Y.

Four light sources, not shown, are arranged in the writing unit **100**. The light sources are respectively modulated by image signals representative of cyan, magenta, yellow and black. The resulting light beams issuing from the light sources are incident to four points on the polygonal mirror **70**. The mirror **70** steers the incident light beams in the direction perpendicular to its axis of rotation. The drums **8**K–**8**Y are stacked in the direction in which the mirror **70** steers the incident light beams.

The light beam representative of a black component and steered by the polygonal mirror **70** is incident to the drum **8**K via an f-θ lens **73**, mirrors **74** and **75**, an elongate lens **76**, a mirror **77** and the opening **100**K. The light beam representative of a cyan component and steered by the polygonal mirror **70** is incident to the drum **8**C via the fe lens **73**, mirrors **78** and **79**, an elongate lens **80**, a mirror **81** and the opening **100**C. The light beam representative of a magenta component and steered by the polygonal mirror **70** is incident to the drum **8**M via an f-θ lens **83**, mirrors **84** and **85**, an elongate lens **86**, a mirror **87** and the opening **100**M. Further, the light beam representative of a yellow component and steered by the polygonal mirror **70** is incident to the drum **8**Y via the f-θ lens **83**, mirrors **88** and **89**, an elongate lens **90**, a mirror **91** and the opening **100**Y. As shown in FIG. **34**B, the openings **100**K–**100**Y each are covered with a dust-proof glass **130**.

As stated above, in the writing unit **100**, the polygonal mirror **70** steers the incident light beams in the same direction as the direction in which the drums **8**K–**8**Y are stacked. The writing unit **100** can therefore be implemented as a single horizontally flat box and can reduce the space requirement, compared to the four writing means **104**K–**104**Y shown in FIG. **9**. Moreover, the number of polygonal mirrors that generate heat is reduced from four to one, so that temperature inside the apparatus can be maintained low.

EXAMPLE 8

FIGS. **35** and **36** show an eighth example of the illustrative embodiment relating to an arrangement for mounting the writing unit of FIGS. **34**A and **34**B to the apparatus. As shown, a flat structural member **92** for supporting the writing unit **100** extends in parallel to the direction in which the cartridges **4–7** are stacked, i.e., in the up-and-down direction. The structural member **92** is affixed to the front wall **22***a*, rear wall **22***b*, top wall **22***e* and bottom wall **22***f*.

The structural member **90** includes four seats **92***a*. The writing unit **100** is mounted to the seats **92***a* by bolts or mounting means **94**. In this configuration, the writing unit **100** and drums **8**K–**8**Y are held at a preselected distance from each other. The seats **92***a* may be omitted, if desired.

The structural member **92** affixed to the walls **22***a*, **22***b*, **22***e* and **22***f* of the frame increases the rigidity of the entire apparatus body **22**. This, coupled with the fact that the writing unit **100** is mounted on the structural member **92**, effectively obviates banding.

EXAMPLE 9

In the example shown in FIGS. **35** and **36**, the structural member **92** is usually formed of metal while the frame of the writing unit **100** is formed of resin. The polygonal scanner included in the writing unit **100** and constituting a heat

source causes the structural member **92** and frame to expand due to heat during operation. When the writing unit **100** thermally expands, the structural member **92** also thermally expands. Because the frame of the writing unit **100** and structural body **92** are different in material and therefore in the coefficient of thermal expansion, the writing unit **92** is apt to deform, i.e., to curve in its intermediate portion without its affixed ends being displaced.

For example, in FIGS. **34**A and **34**B, assume that the writing unit **100** tends to expand in the up-and-down direction with its upper end lower end being restricted by the structural member **92**. Then, the intermediate portion of the writing unit **100** in the up-and-down direction curves away from the drum side. As a result, the mirror **77**, for example, is displaced due to the deformation of the writing unit **100**, shifting the path of the light beam Lb by an angle β. Although the angle β itself is not great, it is magnified before reaching the drum. Because the shift of the light beam Lb differs from one drum to another drum, image components of different colors expected to form a full-color image are brought out of register and lower image quality. The ninth example to be described is constructed to reduce the displacement of the writing unit **100** as far as possible.

Briefly, in this example, the upper and lower ends of the writing unit **100** each are retained by the structural member **92** via a resilient member with a margin with respect to movement in the up-and-down direction. Specifically, as shown in FIG. **37**, the writing unit **100** is formed with a seat **100***a* at its upper end. A hole **140** is formed throughout the seat **100***a*. A bolt **94** is passed through the opening **140** with the intermediary of a resilient washer **96** and screwed into the structural member **92**. A compression spring **95** is loaded between the structural member **92** and the seat **100***a*. The hole **140** has a diameter D greater than the diameter d of the bolt **94**, implementing a margin for the writing unit **100** to move up and down. The above configuration is also applied to the lower end of the writing unit **100**.

In the above construction, when the writing unit **100** thermally expands during operation, it is capable of moving in the up-and-down direction within the range of the difference between the diameters D and d. It follows that the writing unit does not curve, as indicated by a dash-and-dots line in FIG. **37**, but simply expands in the up-and-down direction. This is successful to reduce the displacement of the light beam Lb.

FIG. **38** shows a modification of the above example. As shown, a bolt **97** is screwed into the seat **92** included in the structural member **92**. A spring or resilient member **98** is loaded between the seat **100***a* and the head of the bolt **94**. Again, the hole **140** has a greater diameter than the bolt **97** so as to provide the writing unit **100** with a margin with respect to movement in the up-and-down direction.

The above example and its modification each elastically fasten the structural member **92** and writing unit **100** and provide the writing unit **100** with the above margin, thereby reducing the displacements of the light beams which would bring colors out of register.

EXAMPLE 10

The configurations described with reference to FIGS. **35** and **38** free the writing unit **100** from curve-like deformation, but cannot-fully obviate the displacement in the up-and-down direction. A tenth example to be described further reduces the displacement in the up-and-down direction.

Specifically, as shown in FIGS. **38** and **39**, the intermediate portion of the writing unit **100** in the up-and-down direction are supported by the structural members **92** at two horizontally spaced points, i.e., via two pins **99**. In this condition, the displacement of the writing unit **100** ascribable to thermal expansion is divided into the upper half and lower half. This further reduces irregularity in color ascribable to thermal expansion.

EXAMPLE 11

This example is similar to the example of FIG. **19** and connects the horizontal stays **25** shown in FIGS. **1**A-**6** and assigned to the cartridges **4**–**7** to the structural member **92** described with reference to FIGS. **35**–**39**. Specifically, the stays **25** effectively obviating the vibration of the cartridges **4**–**7** are connected to the structural member **92** perpendicular to the stays **25** and supporting the writing unit **100**. The resulting apparatus body **22** achieves greater rigidity and obviates banding more positively.

EXAMPLE 12

As shown in FIG. **42**, photoconductive drums **8**K", **8**C", **8**M" and **8**Y" are supported beforehand. As shown in FIGS. **43**A–**43**D, cartridges **4**", **5**", **6**" and **7**" do not support any drum. As shown in FIG. **50**, when the cartridges **4**"–**7**" are mounted to the apparatus body **22**, a part of the image forming means, e.g., the rings **10**C"-**1** and **10**C"-**2** (FIG. **50**) contact the drum **8**C". Even with this type of apparatus, it is possible to increase the rigidity of the apparatus. body **22** to thereby obviate banding by connecting the horizontal stays **25** to the structural member **92** of FIGS. **35**–**39**, as shown in FIG. **42**.

EXAMPLE 13

This example applies the guides **27**K–**27**Y shown in FIGS. **2**A to **2**B to the cartridges shown in FIGS. **41**–**43**D.

EXAMPLE 14

This example applies the leaf springs **28**U and **28**D shown in FIGS. **3**A, **3**B, **4**A, **4**B and **6** to the cartridges shown in FIGS. **41**–**43**D.

EXAMPLE 15

This example provides the stays **25** of FIGS. **41**–**43**D with the vibration-proof rubber blocks shown in FIGS. **4**A, **4**B and **7** and exerting viscoelastic pressing forces.

While the above description has concentrated on the characteristic configurations of the illustrative embodiments, the characteristic configurations may be combined as far as possible in order to further enhance the anti-vibration function.

In summary, it will be seen that the present invention provides an image forming apparatus capable of effectively obviating banding ascribable to the vibration of image forming cartridges and optical writing means and members to which they are affixed. In addition, the image forming apparatus of the present invention is miniature, low cost and easy to operate.

Various modifications will become possible for those skilled in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

What is claimed is:

1. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack; and

a structural member for partitioning off a space between nearby ones of said plurality of image forming cartridges mounted to said apparatus body;

wherein a plurality of photoconductive elements each are supported by a respective one of said plurality of image forming cartridges beforehand, or said plurality of photoconductive elements are supported by said apparatus body beforehand such that when said plurality of image forming cartridges are mounted to said apparatus body, said image forming means supported by said image forming cartridges beforehand each partly contact an associated one of said plurality of photoconductive elements;

wherein said structural member includes pressing means for exerting a resilient pressing force between the nearby image forming cartridges and said structural member.

2. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack; and

a structural member for partitioning off a space between nearby ones of said plurality of image forming cartridges mounted to said apparatus body;

wherein a plurality of photoconductive elements each are supported by a respective one of said plurality of image forming cartridges beforehand, or said plurality of photoconductive elements are supported by said apparatus body beforehand such that when said plurality of image forming cartridges are mounted to said apparatus body, said image forming means supported by said image forming cartridges beforehand each partly contact an associated one of said plurality of photoconductive elements;

wherein said structural member includes vibration proofing means for exerting a viscoelastic pressing force between the nearby image forming cartridges and said structural member.

3. An image forming apparatus comprising:

an apparatus body;

a plurality of optical writing means stacked one above the other and each being mounted on a respective base member supported by said apparatus body;

adjusting means included in at least one of said plurality of optical writing means for correcting a shift of a scanning line relative to scanning lines of the other optical writing means;

a structural member partitioning off a space between the optical writing means including said adjusting means and the optical writing means adjoining said optical writing means, said structural member being affixed to said apparatus body at a part thereof; and

vibration proofing means for exerting a viscoelastic pressing force between said optical writing means including said adjusting means and said structural member assigned to said optical writing means.

4. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack;

a plurality of photoconductive elements mounted on said apparatus body one above the other; and

a plurality of optical writing means each for forming a latent image on a respective one of said plurality of photoconductive elements;

wherein said plurality of optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward said plurality of photoconductive elements, and

wherein said image forming means are supported by said image forming cartridges and one or more of said image forming means partly contacts an associated one of said plurality of photoconductive elements,

wherein said writing unit comprises at least a polygonal mirror and a mirror for reflection, said polygonal mirror steering the light beams in said writing unit in a stacking direction of photoconductive elements,

wherein said writing unit is mounted on a flat structural member parallel to the stacking direction of said one of said plurality of photoconductive elements, said structural member being affixed to said apparatus body at a part thereof to thereby maintain a distance.

5. An apparatus as claimed in claim **4**, wherein said writing unit is retained by said structural member via resilient members at both ends thereof in the stacking direction of said one of said plurality of photoconductive elements, said writing unit being provided with a margin with respect to a movement in said stacking direction at portions thereof retained by said structural member.

6. An apparatus as claimed in claim **5**, wherein said writing unit is supported by said structural member at an intermediate point in said stacking direction.

7. An apparatus as claimed in claim **4**, wherein said plurality of image forming cartridges each including one of said photoconductive elements are mounted on said apparatus body, a plurality of structural members each partitioning off a space between nearby ones of said plurality of image forming cartridges and connected to said structural member assigned to said writing unit.

8. An apparatus as claimed in claim **4**, wherein said plurality of image forming cartridges are mounted to said apparatus body such that a part of image forming means included in each of said plurality of image forming cartridges contacts a respective one of said photoconductive elements, a plurality of structural members assigned to said image forming cartridges each partitioning off a space between nearby ones of said plurality of image forming cartridges and connected to said structural member assigned to said writing unit.

9. An apparatus as claimed in claim **8**, wherein said structural members assigned to said image forming cartridges each include a guide engageable with a preselected portion of the respective image forming cartridge for guiding said respective image forming cartridge.

10. An apparatus as claimed in claim **8**, wherein said plurality of structural members assigned to said image forming cartridges each include pressing means for exerting a resilient force between the nearby image forming cartridges and each of said plurality of structural members.

11. An apparatus as claimed in claim **8**, wherein said structural members assigned to said image forming cartridges each include vibration proofing means for exerting a viscoelastic pressing force between the nearby image forming cartridges and the plurality of structural members.

12. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack; and

a plurality of optical writing means each for forming a latent image on a photoconductive element associated therewith;

wherein a plurality of photoconductive elements each are supported by a respective one of said plurality of image forming cartridges beforehand, or said plurality of photoconductive elements are supported by said apparatus body beforehand such that when said plurality of image forming cartridges are mounted to said apparatus body, said image forming means supported by said image forming cartridges beforehand each partly contact an associated one of said plurality of photoconductive elements; and

wherein said plurality of optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward said plurality of photoconductive elements in a stacking direction of said plurality of image forming cartridges, said writing unit being spaced from said plurality of photoconductive elements by a preselected distance,

wherein said writing unit comprises at least a polygonal mirror and a mirror for reflection, said polygonal mirror steering the light beams in said writing unit in a stacking direction of photoconductive elements,

wherein said writing unit is mounted on a flat structural member parallel to the stacking direction of said plurality of photoconductive elements, said structural member being affixed to said apparatus body at a part thereof to thereby maintain said distance,

wherein said writing unit is retained by said structural member via resilient members at both ends thereof in the stacking direction of said plurality of photoconductive elements, said writing unit being provided with a margin with respect to a movement in said stacking direction at portions thereof retained by said structural member.

13. An apparatus as claimed in claim 12, wherein said writing unit is supported by said structural member at an intermediate point in said stacking direction.

14. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack; and

a plurality of optical writing means each for forming a latent image on a photoconductive element associated therewith;

wherein a plurality of photoconductive elements each are supported by a respective one of said plurality of image forming cartridges beforehand, or said plurality of photoconductive elements are supported by said apparatus body beforehand such that when said plurality of image forming cartridges are mounted to said apparatus body, said image forming means supported by said image forming cartridges beforehand each partly contact an associated one of said plurality of photoconductive elements; and

wherein said plurality of optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward said plurality of photoconductive elements in a stacking direction of said plurality of image forming cartridges, said writing unit being spaced from said plurality of photoconductive elements by a preselected distance,

wherein said writing unit comprises at least a polygonal mirror and a mirror for reflection, said polygonal mirror steering the light beams in said writing unit in a stacking direction of photoconductive elements,

wherein said writing unit is mounted on a flat structural member parallel to the stacking direction of said plurality of photoconductive elements, said structural member being affixed to said apparatus body at a part thereof to thereby maintain said distance,

wherein said plurality of image forming cartridges each including one of said photoconductive elements are mounted on said apparatus body, a plurality of structural members each partitioning off a space between nearby ones of said plurality of image forming cartridges and connected to said structural member assigned to said writing unit.

15. An image forming apparatus for forming an image on a photoconductive element with image forming means, comprising:

an apparatus body;

a plurality of image forming cartridges removably mounted to said apparatus body in a form of a stack; and

a plurality of optical writing means each for forming a latent image on a photoconductive element associated therewith;

wherein a plurality of photoconductive elements each are supported by a respective one of said plurality of image forming cartridges beforehand, or said plurality of photoconductive elements are supported by said apparatus body beforehand such that when said plurality of image forming cartridges are mounted to said apparatus body, said image forming means supported by said image forming cartridges beforehand each partly contact an associated one of said plurality of photoconductive elements; and

wherein said plurality of optical writing means are constructed into a single box-like writing unit for emitting a plurality of light beams toward said plurality of photoconductive elements in a stacking direction of said plurality of image forming cartridges, said writing unit being spaced from said plurality of photoconductive elements by a preselected distance,

wherein said writing unit comprises at least a polygonal mirror and a mirror for reflection, said polygonal mirror steering the light beams in said writing unit in a stacking direction of photoconductive elements,

wherein said writing unit is mounted on a flat structural member parallel to the stacking direction of said plurality of photoconductive elements, said structural member being affixed to said apparatus body at a part thereof to thereby maintain said distance,

wherein said plurality of image forming cartridges are mounted to said apparatus body such that a part of image forming means included in each of said plurality of image forming cartridges contacts a respective one of said photoconductive elements, a plurality of structural members assigned to said image forming car-

tridges each partitioning off a space between nearby ones of said plurality of image forming cartridges and connected to said structural member assigned to said writing unit.

16. An apparatus as claimed in claim **15**, wherein said plurality of structural members assigned to said image forming cartridges each include a guide engageable with a preselected portion of the respective image forming cartridge for guiding said respective image forming cartridge.

17. An apparatus as claimed in claim **15**, wherein said plurality of structural members assigned to said image forming cartridges each include pressing means for exerting a resilient force between the nearby image forming cartridges and the plurality of structural members.

18. An apparatus as claimed in claim **15**, wherein said plurality of structural members assigned to said image forming cartridges each include vibration proofing means for exerting a viscoelastic pressing force between the nearby image forming cartridges and the plurality of structural members.

* * * * *